

- Certificate / ProductInformation -

**RAVENOL FES SAE 0W-30**

Art. 1111146

FULLY SYNTHETIC

USVO® & CleanSynto®

**Description:**

**RAVENOL FES SAE 0W-30** is a PAO (Polyalphaolefin) based, fully synthetic low friction motor oil with especially USVO® and proven CleanSynto® technology for passenger car petrol and diesel engines with and without turbo-charging and direct injection.

Due to the USVO® technology we achieve an extremely high viscosity stability. We avoid the disadvantages of polymeric viscosity improvers while taking advantage of them. This improves engine protection, performance, engine cleanliness and oil drain intervals. The USVO® technology makes it possible that the product has no shear losses during the entire change interval and is extremely stable to oxidation. This unique technology helps oil to be lubricated faster, thereby minimizing friction while keeping the engine clean and efficient.

**RAVENOL FES SAE 0W-30** utilizes the positive properties of tungsten to smooth the surface structure of the motor, reducing friction and wear, and significantly improving mechanical efficiency.

**RAVENOL FES SAE 0W-30** is based on additives with low ash content for use in modern passenger car with diesel and gasoline engines with excellent cold start characteristics, low oil consumption and reduced pollutant emissions. This oil will increase the DPF and TWC life. HTHS >2,9mPa.s. Developed for fuel economy especially for the latest petrol and diesel engines of BMW, PSA, FIAT, IVECO and Jaguar Land Rover.

With its new formulation, **RAVENOL FES SAE 0W-30** provides a safe layer of lubrication even at very high operating temperatures and protects from corrosion and loss of oil through oxidation or coking. The excellent cold start behavior ensures optimum lubrication safety during the cold running phase.

By significantly reducing fuel consumption, **RAVENOL FES SAE 0W-30** helps to protect the environment by reducing emissions.

**RAVENOL FES SAE 0W-30** minimizes friction, wear and fuel consumption with excellent cold start characteristics.

Extended oil change intervals according to the manufacturer's instructions.

**Application Directions:**

**RAVENOL FES SAE 0W-30** is a universal fuel economy, especially designed engine oil for modern gasoline and diesel engines with and without turbo charger in passenger cars and vans with extended oil change intervals of BMW, PSA, FIAT, IVECO and Jaguar Land Rover. Extends the lifespan of the particle filter. Due to the specific composition is **RAVENOL FES SAE 0W-30** excellent suitable for use for indicated OEM requirements.

**Quality Classification:**

**RAVENOL FES SAE 0W-30** is tried and tested for aggregates specifying:

Specifications: ACEA C2

Approval: BMW Longlife-12FE

Recommendations: Chrysler MS-13340; FIAT 9.55535-DS1/GS1; IVECO 18-1811 CLASSE SC1 LV; Jaguar Land Rover STJLR.03.5007; PSA B71 2290, B71 2312

## - Certificate / ProductInformation -

### RAVENOL FES SAE 0W-30

Art. 1111146

FULLY SYNTHETIC

USVO® & CleanSynto®

#### Technical Characteristics:

RAVENOL FES SAE 0W-30 offers:

- Fuel economy in part and full power operation
- Excellent wear protection and high viscosity index also under high-speed driving conditions, the long life of the engine
- Excellent cold starting characteristics also at low temperatures
- A safe lubricant film at high operating temperatures
- Low evaporative tendency, so lower oil consumption
- No deposits in combustion chambers, in the piston ring zone and valves because of oil conditioned
- Neutrality towards sealing materials
- Extended oil change intervals to protect natural resources

#### Technical Values:

Characteristics	Unit	Data	Test according to
Density at 20°C	kg/m³	844,0	EN ISO 12185
Colour		yellow brown	visual
Viscosity at 100°C	mm²/s	10,0	DIN 51562-1
Viscosity at 40°C	mm²/s	55,1	DIN 51562-1
Viscosity Index VI		171	DIN ISO 2909
HTHS Viscosity at 150°C	mPa*s	3,0	ASTM D5481
CCS Viscosity at -35°C	mPa*s	4600	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -40°C	mPa*s	15.200	ASTM D4684
Pourpoint	°C	-57	DIN ISO 3016
Noack Volatility	% M/M	9,0	ASTM D5800
Flashpoint	°C	236	DIN ISO 2592
TBN	mg KOH/g	8,5	ASTM D2896
Sulphated ash	%wt.	0,8	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.