Ravensberger Schmierstoffvertrieb GmbH Joellenbecker Strasse 2 33824 Werther

Tel.: 05203/9719-0 Fax.: 05203/9719-42

- Certificate / ProductInformation -

RAVENOL SNOWMOBILES Fullsynth. 2-Takt

Art. 1151310

FULLY SYNTHETIC WINTER

Description:

RAVENOL SNOWMOBILES Fullsynth. 2-Takt is high quality blue coloured fully synthetic two-stroke engine oil especially developed for 2-stroke snowmobiles.

RAVENOL SNOWMOBILES Fullsynth. 2-Takt with special esters and Polyisobutylene (PIB) and effectively low ash additives.

Application Directions:

RAVENOL SNOWMOBILES Fullsynth. 2-Takt can generally be mixed with regular petrol 1:100.

RAVENOL SNOWMOBILES Fullsynth. 2-Takt is used for lubrication of air-cooled two-stroke petrol engines with very high speed and heaviest load.

RAVENOL SNOWMOBILES Fullsynth. 2-Takt is also suitable for the lubrication of two stroke scooters with water cooling.

Quality Classification:

RAVENOL SNOWMOBILES Fullsynth. 2-Takt is tried and tested for aggregates specifying:

Specifications: API TD; ISO-L-EGD Approval: JASO FD (049RAV154)

Recommendations: Arctic Cat; Bombardier; Kawasaki; Rotax 253; Suzuki; Yamaha

Technical Characteristics:

RAVENOL SNOWMOBILES Fullsynth. 2-Takt offers:

- A proper lubrication of all engine parts
- A strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from combustion residues and deposits
- Clean spark plugs provide optimal performance of the engines
- A very high wear and corrosion protection
- Low exhaust emission levels by good combustion
- Very low Pourpoint, also to use at very low temperature

Technical Values:

Characteristics	Unit	Data	Test according to
Density at 20°C	kg/m³	873,0	EN ISO 12185
Colour		blue	visual
Viscosity at 100°C	mm²/s	9,4	DIN 51562-1
Viscosity at 40°C	mm²/s	55,15	DIN 51562-1
Viscosity Index VI		154	DIN ISO 2909
Pourpoint	°C	-57	DIN ISO 3016
Flashpoint	°C	128	DIN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems occur please consult a technician.

14.09.20 Page 1 from 1