

- Certificate / ProductInformation -

RAVENOL Standard Truck SAE 10W

Art. 1123610

MINERAL

TRUCK

Description:

RAVENOL Standard Truck SAE 10W is mineral mono grade motor oil for trucks. All-season oil for all truck diesel engine types. High protection against friction and abrasion, excellent cold start characteristics. Extended oil change intervals according to manufacturer's recommendations.

Application Directions:

RAVENOL Standard Truck SAE 10W is mono grade motor oil for use in truck diesel engines. Also suitable for stationary plants.

Quality Classification:

RAVENOL Standard Truck SAE 10W is tried and tested for aggregates specifying:

Specifications: API CF/SF

Recommendations: MB 227.0, Caterpillar TO-2, Allison C4, MIL-L2104 E, MAN 270, MTU Typ 1, Voith Retarder A, Voith DIWA, ZF TE-ML 02C, 03B, 04B, 06A, 07D

Technical Characteristics:

RAVENOL Standard Truck SAE 10W offers:

- Good shear stability
- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts

Technical Values:

Characteristics	Unit	Data	Test according to
Density at 20°C	kg/m ³	862,0	EN ISO 12185
Colour		yellow brown	visual
Viscosity at 100°C	mm ² /s	6,4	DIN 51562-1
Viscosity at 40°C	mm ² /s	36,9	DIN 51562-1
Viscosity Index VI		123	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	232	DIN ISO 2592
TBN	mg KOH/g	21,0	ASTM D2896

All indicated data are approximate values and are subject to the commercial fluctuations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems occur please consult a technician.

07.06.18

Page 1 from 1