

- Certificate / ProductInformation-

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40

Art. 1117100

MINERAL

HIGH MILEAGE

Description:

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 is particularly recommended for vehicles with high mileage petrol and diesel engines with and without turbocharge and direct injection. The mineral motor oil **RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40** is a new development with a unique formula specifically for high mileage vehicles of approx. 100,000 km and more.

The extremely conditioning and cleaning agents in **RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40** revitalise critical engine parts and particularly protect gaskets. This can extend the life, particularly in older vehicles with high mileage.

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 features outstanding lubrication and excellent shear stability, and the added conditioners simultaneously reduce oil consumption and protect from sludge and wear.

Application Directions:

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 is perfectly suited for year-round use in high mileage petrol and diesel engines with 100,000 km and more, and promotes low oil consumption. A very clean engine is guaranteed. **RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40** extends the life of the engine in older vehicles by reducing oil consumption and protecting from sludge and wear. A very clean engine is guaranteed.

Quality Classification:

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 tried and tested for aggregates specifying:

Specifications: API SJ/CF, ACEA A3/B4

Recommendations: MB 229.1, MAN 271, ZF TE-ML 07C, VW 505 00

Technical Characteristics:

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 offers:

- High wear protection, important for large mileages and inadequate oil changes
- Outstanding detergent and dispersant properties prevent sludge
- High oxidation stability for a long life
- Brilliant cold cranking behaviour through special additives
- Excellent viscosity-temperature behaviour
- Low vaporisation characteristics, therefore reduced oil consumption
- Suitable for catalytic converters

- Certificate / ProductInformation-

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40

Art. 1117100

MINERAL

HIGH MILEAGE

Technical Values:

Characteristics	Unit	Data	Test according to
Density at 20°C	kg/m³	873,0	EN ISO 12185
Colour		yellow brown	visual
Viscosity at 100°C	mm²/s	14,4	DIN 51562-1
Viscosity at 40°C	mm²/s	107,2	DIN 51562-1
Viscosity Index VI		137	DIN ISO 2909
CCS Viscosity at -20°C	mPa*s	6200	ASTM D5293
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	240	DIN ISO 2592
TBN	mg KOH/g	8,9	ASTM D2896
Sulphated ash	%wt.	1,1	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.